



Silk Screen Inks

Products Information

www.sabinecolors.com



Oblique Arm Plane Screen Printing Machinery SS-5070S - SS-7010S



Applying Scope:

It applied to the plain screen printing of membrane, card, and board of different materials in different thickness.

Main Characteristic

Oblique arm structure, the drive of the printing arm lift and the printing process are respectively.

Stainless printing platform, in which evenly distributing fine vacuum absorbing hole ϕ 1.0~1.5

Powerful automatic vacuum absorbing.

The printing platform can be micro adjusted in level and uprightness direction, and accurate multi-color register.

The lift of the printing platform adopts the combination of frequency conversion system and reducer, the speed is adjustable.

The printing blade frame adopts frequency drag system, chain

transmission, the printing speed and ink reclaiming speed can be adjusted and controlled respectively.

Air- drive screen thrown equipments, effectively prevent the adhering to the screen.

2 group/ 4 cylinders ensures the steady pressure of the printing and ink reclaiming. The squeegee and the ink reclaiming blade switched automatically

The angle of the printing and ink reclaiming are adjustable. And the handling is very convenient.

Item	SS-7010S
Printing Dimension	700×1000mm
Platform Dimension	850×1200mm
Max Frame	1000×1400
Platform Precision	±0.15 mm
Substrate Thickness	50mm
Printing Drive W	400 Frequency conversion
Printing Pressure	5.0~7.0 Kgf/cm ²
Capacity	800 pc/ hour
Power	380V/2.7KW
Dimension	1900×1200×1450mm

Item	SS-5070S
Printing Dimension	500×700mm
Platform Dimension	650×800mm
Max Frame	850×900
Platform Precision	±0.1 mm
Substrate Thickness	50mm
Printing Drive W	400 Frequency conversion
Printing Pressure	4.0~6.0 Kgf/cm ²
Capacity	1100 pc/ hour
Power	380V/2.7KW
Dimension	1700×1150×1450mm