

## Silk Screen Inks **Product Information**

### Support MicroPiezoelectric DX5 DX7 Print-head Mesent Completely High-precision High-precision Color Perfect Gradient Colors

ML-130S



#### Technology of the fifth print head

Using Variable—Sized Droplet Technology (VSDT), Using 2-bit files while doing RIP treatment. Change the size of droplet according to the image changes in real time and using the bigger droplets to print solid area, the smaller droplets is used to express fine gradation of tones and details. VSDT provides a perfect balance between speed and the quality of image to enhance

the print speed and accuracy.



DX5 print head



Dx7 print head




DX5 print head

#### Epoch-making outstanding printing


High Precision inkjet: The highest precision is 1440dpi and the variable dot technology.

High quality printing is made of three different sizes ofink dots. Even in the four-color mode, it also can present a very good quality.



#### Three-stage heating system

The printer outdoor solvent series equipment has before printing, printing and after printing automatic intelligent heating system.controls the temperature precisely and the temperature rise quickly and controlled in 30 – 50 °C. The ink and media combines fully and the bright colors of the ink shows completely.



#### **Product Features**

The highest precision is 1440 dpi and the variable dot technology.

speed

High great precision is 1440 dpi and the variable dot technology.

High quality printing is made of three different sizes of ink-dots...Even in the four—color mode, it also can present a very good quality.

Automatic test paper, automatic cutting: using the patten sensor measure can measure the media position effectively, set the starting point automatic elly and cutting automatically.

Supports color GAD output directly, customers can have color image output device while they already have aindour and outdoor photo output devices, it's good for enterprise to propagate.

Automatic seamless mosaic; completely realize the fixed automatic screen printing and the mosaic picture of the wireless length.

Three—stage heating system: Before printing, printing and after printing, the three—stage automatic intelligent heating system, control temperature precisely. The ink and media combines fully and the bright colors of the link is shows completely.

The outling link concentration the user can adjust the concentration based on the variety of link according to the characteristics of the machine.

The outing link concentration: the user can adjust the concentration based on the variety of link according to the characteristics of the machine environment to prevent the ink from causing the ink break.

7. Maintenance Station: streamlining follower lift maintenance station structure fully reflects the high sealing, corrosion resistance, so that the

nozzle is always in good condition.

Brushless DO motor; brushless DO motor drive the car and at the same time keep high=precision printing reflect long motor life, the motor system is more stable and durable.

Induction and paper system: realized the customers? large material output or select more types of media, the stability and precision of paper



# Silk Screen Inks Product Information

## ML-130S

Item Model		Specifications		
		ML-90HS	ML-90IS	ML-130S
Print Head		Piezo Technology, Epson DX5 Dx7 Print head (180 nozzles x 8 lines) x 1 pcs	Piezo Technology, Epson DX5 Dx7 Print head (180 nozzles x 8 lines) x 1 pcs	Piezo Technology, Epson DX5 Dx7 Print head (180 nozzles x 8 lines) x 1 pcs
Print Resolution		450dpi -540dpi - 600dpi - 720dpi - 1080dpi - 1440dpi		
Ink	Color	2 x 4 C.M.Y.K	2 x 4 C.M.Y.K	2 x 4 C.M.Y.K
	Sort	Water Based ink / Echo Solvent ink	Water Based ink / Echo Solvent ink	Water Based ink / Echo Solvent ink
	Ink Supply System	CISS Ink Supply System	CISS Ink Supply System	CISS Ink Supply System
Print Speed	Draft	3 1 m <sup>2</sup> / H	3 3 m² / H	2 9 m² / H
	Text	24 m <sup>2</sup> / H	2 6 m² / H	2 2 m² / H
	Picture	1 6 m² / H	18 m² / H	1 4 m² / H
	Photo	1 0 m <sup>2</sup> / H	1 2 m² / H	8 m² / H
Media	Size	1520 m m	1830 m m	1 3 0 0 m m
	Туре	Inside: PP Synthetic Paper, Vinyl Sheet, Film, Gloss Photo Paper, Coated Paper, Canvas, Parchment Paper		
		Outdoor: Stickers Vinyl, Light cloth, Leather, Canvas, Wall paper, Outdoor Coated Paper, Outdoor PP		
	Transfer	Inside: Automatic damping send cloth system		
		Outdoor: Induction tension retractable paper system		
Media Cutting		Auto / Manual Cut	Auto / Manual Cut	Auto / Manual Cut
Media Heater		Pre print / Post heater	Pre print / Post heater	Pre print / Post heater
USB Transfer Interface		USB2.0 High-speed	USB2.0 High-speed	USB2.0 High-speed
Power		AC 110V (± 10%) 50/60Hz AC 110V (± 10%) 50/60Hz		
Operation Environment		(Temperature) : 15°c ~25°c, (Humidity) : 35%RH ~ 65%RH		
Dimension (WxDxH)		2430mm x 650mm x 560mm	2670mm x 650mm x 570mm	2100mm x 650mm x 510mm
Weight		145kg	165kg	117kg



Brush less DC Motor



**Automatic Cutter** 



**Maintenance Station** 



Streamline Follower Lift Tension Induced Folding Paper System